

Conference tables with electric height adjustment technical specification



.mdd

MDD has a leading position among manufacturers of office furniture with many awards that prove quality and continuously increase demand for its products.

The realities of today's market require constant quality improvement at all levels of modern organization. This applies in particular to customer service, marketing, quality of products and also to quality of processes within the company. Partnership relations among employees and with business partners form a base of economic growth and success of the company.

Constant investments in innovative machinery park, optimization of management systems and an expansion of production halls allow to minimize the lead times for the product of the highest quality.

More than twenty years of experience in office furniture industry come with reference from a long list of companies and institutions to show their appreciation for an efficient and comprehensive service.

MDD is highly aware of the environment.

Being located in the forest region with lake by its side, MDD takes the nature seriously and invests constantly in a modern and energy-efficient solutions to preserve the local life. Company puts emphasis on waste segregation and recycling. MDD has been awarded for the exceptional care and involvement in waste disposal. All materials used are environmentally friendly and enjoy a high 95 % rate of being recycled.



General informations:

Warranty:

MDD products - **5 years.**

Electrical components and fabric - **2 years.**

Certificate - MFC:



Boards density:

12 mm - 690 - 750 kg/m³

18 mm - 650 - 690 kg/m³

28 mm - 610 - 630 kg/m³

36 mm - 610 - 630 kg/m³


Assembly:

product delivered in separate elements

Packing:


cartboard, perforated plastic mesh wrap

Conference tables with electric height adjustment




1. **Worktop** - MFC 28 mm, ABS edge
2. **Control panel** - 2 pcs/ table
3. **Leveling feet** - range 5 mm
4. **Metal element for legs connecting**
5. **Electric height adjustable frame** - powder coated steel, load 100 kg, telescopic leg:
 - adjustment range 650-1300 mm - telescopic leg - 3 profiles
 - adjustment range 700-1200 mm - telescopic leg - 2 profiles

Control panel




1. **Frame technical specification:**
 - **Height adjustment** - 40 mm/sec Super Soft Start - Stop
 - **Drive** - 2 synchronised motors with microprocessor, work control sensor
 - **Noise level** - < 48dB
 - **Anti collision mechanism**
 - **Control panel** - stepless height adjustment, OPTION WITH EXTRA CHARGE - adjustment with 4 heights memory
 - **Standards** - ISO 21016, EN 527-2, EN 527-3
 - **EU Directives** - 206/95EC, UI508 1999, UL 1004 R7 06, WE DC 2004/108WE
 - **Power supply** - 230V, 300W, power consumption on Standby - 0.3W

Conference tables with electric height adjustment



BOD622
2200 / 1200 / 1300-650
99.26 kg



BOD522
2200 / 1200 / 1200-700
94.2 kg

Top

			
14 Beech	26 Aluminum satinato	31 Canadian oak	34 Chestnut
			
39 Polar birch	64 Cocoa	67 White pastel	106 Lowland walnut
			
154 Anthracite	08 Black	167 Grey oak	168 Natural oak

Frame

			
M009 Aluminum semi-matt RAL9006	M015 White semi-matt RAL9010	M154 Anthracite semi-matt RAL7043	M115 Black semi-matt RAL9005